

Dimension in Millimeters (inches)


Net Weight: 5.6 kg (12.3 lb)

Technical Data


Rated Voltage ($\pm 10\%$)	100~277V AC
Watts ($\pm 10\%$)	30W / 40W / 50W / 60W / 70W / 80W / 90W / 100W / 110W / 120W / 130W / 140W / 150W / 180W / 200W / 250W (250W only for green light)
Amps	0.12A~2.5A
Color of LED Light	3000K (Warm White) / 5000K (Cool White) / Green Light
Ambient Temperature	-20°C ~ +40°C
Power Factor	$\cos \geq 0.9$
CRI	Cool White ≥ 70 / Warm White ≥ 80
Lm / W ($\pm 10\%$)	120lm/w
Beam Angle	X-110° / Y-110°
Frequency	50 / 60 Hz
Degree of Protection	IP67/ NEMA 6
Material	<ul style="list-style-type: none"> Enclosure: Aluminum alloy Cover: Glass or PC (Clear / Matte)
LED Service Life	60,000 hrs
Entrance Thread	1 × NPT 3/4"
Lens Angle	30° / 60° / 90° / 120° / 149°X(25°+90°)

Optical Report

Polar Luminous
Intensity Distribution



Luminous
Intensity Distribution Diagram



Model Code

THT	W	2302	A	N	K	C	H	25	WHT
			①			②		③	

① Series Type

A=With Glass
B=With Clear PC
C=With Matte PC

② C.C.T.

C=Cool White
W=Warm White
G=Green Light

③ Wattage

C0=30W, D0=40W, E0=50W, F0=60W
G0=70W, H0=80W, I0=90W, J0=100W
K0=110W, L0=120W, M0=130W, N0=140W
P0=150W, S0=180W, U0=200W, 25=250W

Mounting Option & Dimensions (All in mm)

